

HYMAX® REDUCER (14" - 60")

Product Specifications

FEATURES

- Using the game-changing HYMAX technology, proven in over 1 million installations in the US
- Suitable for all types of pipes ductile iron, cast iron, steel, copper, PE, PVC, AC, GRP
- Joins pipes of different sizes
- Patented hydraulically-assisted gasket with 2-stage sealing
- Lightweight construction enables fast and easy installation
- Allows 4° dynamic deflection on each end, reducing future pipe damage
- One product can connect pipes of two different materials

SPECIFICATIONS STANDARDS

 HYMAX REDUCER meets or exceeds standards NSF 61, NSF 372.

SIZE

- Available in nominal diameter from 14" 24" standard.
- 26" 60" MTO (made to order). Call Mueller for details.

MATERIALS END RINGS

- 14" 16" ASTM A283/A283M Grade C steel (or ductile iron casting ASTM A536 Grade 65-45-12).
- 18" 60" ASTM A283/A283M Grade C steel.



CENTER RING

• 14" - 60" ASTM A283/A283M Grade C steel

GASKETS

 EPDM and NBR available. Both are compounded for water and sewage, meet international standards for contact with drinking water.

BRIDGE

AISI 304 stainless steel.

SPHERICAL SPACERS

• AISI 304 stainless steel.

COATING

- 100% fusion bonded epoxy for enhanced corrosion protection.
- Nominal thickness 14 mm.

NUTS AND BOLTS

• AISI 304 stainless steel. Rolled thread and anti-galling coating.





REPAIR









PRODUCT PERFORMANCE (*)

WORKING TEMPERATURE

EPDM: -20° F up to +125° F

NBR: -4° F up to +125° F

DYNAMIC DEFLECTION

14" - 18": Up to 4° per side

> 48": Up to 3° per side

VACUUM TEST

12 psi

*See submittal drawings for details.

26" - 60": Call Mueller for details.

WORKING PRESSURE

14" - 16": 260 psi 18" - 24": 232 psi

MAXIMUM OFFSET FOR MISALIGNED PIPES

14" - 60": 0.51"

MAXIMUM OUT OF ROUNDNESS

14" - 60": 0.51"

PRODUCT TABLES

ND 14" - 24" EPDM										
ND (inch)	Torque Side 1 (ft-lb)	Torque Side 2 (ft-lb)								
14x16	150	150								
16x18	150	150								
18x20	150	150								
20x24	150	150								

PRODUCT CONFIGURATIONS

The product is offered in several different configurations. Note that the "xx" marking in the Cat. no. should be replaced as directed:

Part Number 861-XX


56 - Product with EPDM gasket

57 - Product with NBR gasket

For example:

861XX0054008816 should be read as 861560054008816 for EPDM gasket and 861570054008816 for NBR gasket

PRODUCT TABLES



HYMAX REDUCER NOMINAL SIZES 14" - 24"														
HYMAX Part Number	ND (mm)	Overall Range 1 (inch)	Before Removal of the Inner Layer 1 (inch)	After Removal of the Inner Layer 1 (inch)	Overall Range 2 (inch)	Before Removal of the Inner Layer 2 (inch)	After Removal of the Inner Layer 2 (inch)	Bolts Qty. and Size	H1 (inch)	H2 (inch)	L (inch)	Approx. Weight (lbs)		
861560378043416	14 x 16	15.00 - 17.10	15.00 - 16.10	16.02 - 17.10	17.10 - 19.20	17.10 - 18.19	18.11 - 19.20	4 - M16	23.2	25.6	23.8	142		
861560434048816	16 x 18	17.10 - 19.20	17.10 - 18.19	18.11 - 19.20	19.2 0 - 21.30	19.20 - 20.29	20.21 - 21.30	4 - M16	25.6	27.8	23.8	162		
861560488054016	18 x 20	19.20 - 21.30	19.20 - 20.29	20 .21 - 21.30	21.25 - 23.35	21.25 - 22.35	22.27 - 23.35	4 - M16	27.8	29.8	23.8	172		
861560540060616	20 x 24	21.25 - 23.35	21.25 - 22.35	22.27 - 23.35	23.85 - 25.95	23.85 - 24.96	24.88 - 25.95	4 - M16	29.8	31.7	23.8	180		
861560540062416	20 x 24	21.25 - 23.35	21.25 - 22.35	22.27 - 23.35	24.60 - 26.70	24.60 - 25.67	25.59 - 26.70	4 - M16	29.8	33.2	23.8	182		

HYMAX REDUCER NOMINAL SIZES 26" - 60"

26" - 60" - MTO (made to order) is available

To learn more, visit HymaxUSA.com. Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HyMAX®, Krausz®, Jones®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands to learn more. © 2021 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed to extend on a place of the products of the parties. Products about marked with a certion purpled (6) are pulped to parties. Products about marked with a certion purpled (6) are pulped to parties. Products about marked with a certion purpled (6) are pulped to parties. Products a bout marked with a certion purpled (6) are pulped to parties. Products a bout marked with a certion purpled (6) are pulped to parties.

© 2021 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Co., LLC., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

