

# HYMAX<sup>®</sup>

a **MUELLER** brand

## HYMAX<sup>®</sup> PRO DEDICATED SIZE COUPLING Product Specifications (4" - 24")

### TYPICAL APPLICATIONS

- Joining & replacing plain-end pipes with the same outside diameters

### AVAILABLE SIZES

- 4" through 24" nominal
- IPS and DIPS

### PIPE TYPES

- Ductile Iron, Cast Iron, Steel, PVC, AC, and HDPE (Insert Stiffener Required)

### LISTINGS/STANDARDS

- Certified to NSF/ANSI 61 and NSF/ANSI 372
- Meets applicable portions of AWWA C219
- Fusion-Bonded Epoxy Coating meets requirements of AWWA C213

### MATERIALS

- Fusion Bonded Epoxy Coating
- Steel End Rings: Carbon Steel ASTM A283M Grade C
- Center Sleeve: Carbon Steel per ASTM A53 up to 12", QstE380TM 14" - 24"

### GASKET

- EPDM per ASTM D2000
- Working Temperature range: -20°F to 125°F

### BRIDGE

- AISI 304 Stainless Steel

### HARDWARE

- Bolts: AISI 304 Stainless Steel ASTM F593
- Nuts: AISI 304 Stainless Steel ASTM F594
- Coating: Fe/Zn coated per ASTM A1059/A 1059M
- Spherical spacers: ASTM A351-CF8M (equivalent to AISI 304)
- All nuts and bolts shall be Standard American design, ANSI or ASME standard family B18

### WORKING TEMPERATURE

- -20° F up to +125° F

### DYNAMIC DEFLECTION

- Up to 4 degrees per side

### WORKING PRESSURE

- 300 PSI up to 14"
- 250 PSI 16" to 24"



JOIN



REPAIR



RESTRAIN



TAP

**MUELLER**

# HYMAX PRO NOMINAL SIZES (4" - 24")

## HYMAX PRO NOMINAL SIZES (4" - 24")

Hymax Pro Part Number	ND (inch)	Product Range (inch)	Bolts Qty. - Size (inch)	Torque (ft - lbs)	Approx. Weight (lbs)	Length (inch)	Working Pressure (PSI)	Test Pressure (PSI)
771-56-02-04-21	4" DIPS	4.71 - 4.88	2 - 1/16"	45	10.7	7.3	300	450
771-56-02-06-21	6" DIPS	6.81 - 6.97	2 - 1/16"	45	13.7	7.3	300	450
771-56-02-08-21	8" DIPS	8.98 - 9.14	2 - 1/16"	60	17.7	8.2	300	450
771-56-02-10-21	10" DIPS	11.02 - 11.18	2 - 1/16"	60	20.8	8.2	300	450
771-56-01-04-21	4" IPS	4.41 - 4.57	2 - 1/16"	45	10.2	7.3	300	450
771-56-01-06-21	6" IPS	6.54 - 6.70	2 - 1/16"	45	13.2	7.3	300	450
771-56-01-08-21	8" IPS	8.58 - 8.70	2 - 1/16"	60	17.2	8.2	300	450
771-56-01-10-21	10" IPS	10.71 - 10.83	2 - 1/16"	60	20.3	8.2	300	450

Hymax Pro Part Number	ND (inch)	Product Range (inch)	Bolts Qty. - Size (inch)	Torque (ft - lbs)		Approx. Weight (lbs)	Length (inch)	Working Pressure (PSI)	Test Pressure (PSI)
				DI	HDPE/PVC				
771-56-02-12-21	12" DIPS	13.11 - 13.27	4 - 1/16"	60	60	29.3	8.3	300	450
771-56-02-14-21	14" DIPS	15.20 - 15.40	4 - 5/8"	75	75	42.8	10.5	300	450
771-56-02-16-17	16" DIPS	17.30 - 17.50	4 - 5/8"	75	75	52.4	10.5	250	375
771-56-02-18-17	18" DIPS	19.40 - 19.60	4 - 5/8"	75	75	56.8	10.5	250	375
771-56-02-20-17	20" DIPS	21.50 - 21.70	4 - 5/8"	110*	75	61.7	10.5	250	375
771-56-02-24-17	24" DIPS	25.72 - 25.98	4 - 5/8"	145*	95	71.2	10.5	250	375

Hymax Pro Part Number	ND (inch)	Product Range (inch)	Bolts Qty. - Size (inch)	Torque (ft - lbs)		Approx. Weight (lbs)	Length (inch)	Working Pressure (PSI)	Test Pressure (PSI)
				Steel	HDPE/PVC				
771-56-01-12-21	12" IPS	12.68 - 12.84	4 - 1/16"	60	60	28.3	8.3	300	450
771-56-01-14-21	14" IPS	13.94 - 14.14	4 - 5/8"	75	75	42	10.5	300	450
771-56-01-16-17	16" IPS	15.90 - 16.10	4 - 5/8"	75	75	49.2	10.5	250	375
771-56-01-18-17	18" IPS	17.90 - 18.10	4 - 5/8"	75	75	53.7	10.5	250	375
771-56-01-20-17	20" IPS	19.90 - 20.10	4 - 5/8"	75	75	58.1	10.5	250	375
771-56-01-24-17	24" IPS	23.89 - 24.11	4 - 5/8"	95	95	67	10.5	250	375

\*For 20" Ductile Iron Pipe, the maximum allowable torque is 150 ft-lbs

\*\*For 24" Ductile Iron Pipe, the maximum allowable torque is 160 ft-lbs

To learn more, visit [HymaxUSA.com](http://HymaxUSA.com).

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HYMAX®, i2O®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see [muellerwp.com/brands](http://muellerwp.com/brands) to learn more.

© 2022 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Co., LLC., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit [www.mwppat.com](http://www.mwppat.com). These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

