

Drinking Water System Components

COMPANY

KRAUSZ INDUSTRIES LTD

1 HaRav Shalom Mantsura st. 4850001 (3rd Floor)
Rosh HaAyin, Israel

MH49259

NSF/ANSI/CAN 61

Plant at: TEL-AVIV ISRAEL

Mechanical Devices

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl	Surface Area to Volume Ratio
HYMAX TAPPED CLAMP [NSF 600]	23	-	-
HYMAX TAPPED CLAMP WITH PLUG [NSF 600]	23	-	-

Pipes and Related Products

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl
Grip TELESCOPING INSULATING JOINT RESTRAINTS C/C [NSF 600]	23	-
Grip TELESCOPING INSULATING JOINT RESTRAINTS C/F [NSF 600]	23	-
GRIPMAX MJ (1 1/2" to 60") [a] [NSF 600]	23	-
HYJOINT (1-1/2" to 60") [a] [NSF 600]	23	-
HYMAX (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX CLAMP (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI 45 Elbow (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI 90 Elbow (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI End Cap (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI F/A (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI Reducer (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI Slip Joint (Lalo) (1 1/2" to 60") [a] [NSF 600]	23	-

HYMAX DI SWIVELJOINT (Lalo) (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI T C-C-C (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX DI T C-F-C (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX FLANGED (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX FLANGED OUTLET (3" to 72") [a] [NSF 600]	23	-
HYMAX GRIP (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP 45 Elbow (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP 90 Elbow (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP Cut in Sleeve MJ (3" - 12") [a] [NSF 600]	23	-
HYMAX GRIP End Cap (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP F/A (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP Reducer (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP Slip Joint (Lalo) (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP SWIVELJOINT (Lalo) (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP T Grip-F-Grip (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP T Grip-Grip-Grip (1 1/2" to 60") [a] [NSF 600]	23	-
HYMAX GRIP Telescope Flange (3" - 12") [a] [NSF 600]	23	-
HYMAX LONG BODY (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX PRO 4"-24" [NSF 600]	23	-
HYMAX REDUCER (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX VERSA (1 1/2" to 118") [a] [NSF 600]	23	-
HYMAX VERSA ENCAPSULATION (1 1/2" to 3") [a] [NSF 600]	23	-
HYMAX VERSA WIDE 18 (4" to 118") [a] [NSF 600]	23	-
HYMAX VERSA WIDE 24 (12" to 118") [a] [NSF 600]	23	-
HYMAX2 (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX2 FLANGED (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX2 FLANGED OUTLET (3" to 72") [a] [NSF 600]	23	-
HYMAX2 LONG BODY (1 1/2" to 72") [a] [NSF 600]	23	-
HYMAX2 REDUCER (1 1/2" to 72") [a] [NSF 600]	23	-
VERSA MAX (1 1/2" to 118") [a] [NSF 600]	23	-

NSF/ANSI 61

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl
DISMANTLING JOINT (1-1/2" to 60")[a]	23	-
EZMAX (1 1/2" to 60") [a]	23	-

[NSF 600] - Meets health effects requirements of NSF/ANSI/CAN 600.

[a] - Also Classified to NSF/ANSI 372

Trademark and/or Tradename: ""HYMAX a MUELLER brand etc."" , ""HYMAX"" , ""KRAUSZ USA"" , ""KRAUSZ"" , ""MUELLER"" ,



Last Updated on 2023-04-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."